

20 - Trailer - Manual Winches

Stainless Steel Trailer Winches



Single gear drive winch



Dual gear drive winch

Ideal for trailers, docks, pontoons and other general lifting applications (not for lifting humans). High quality rust and corrosion resistant marine hand winches made from 304 grade stainless steel. Features include solid gear design, internally lubricated drum and pinion gear bushings and stainless steel handle with moulded roller grip.

Available in single gear drive or dual gear drive for additional lifting capacity.

Winch cable not included - see next 2 pages.

RWB895 380 kg Single Ratio 3.5:1 Base 125 x 85mm

RWB896 540 kg Dual Ratio 3.5:1 Base 125 x 85mm

RWB897 720 kg Single Ratio 4.1:1 Base 135 x 88mm

RWB898 900 kg Dual Ratio 4.1:1 Base 135 x 88mm

Standard Manual Trailer Winches



RWB2903



RWB2905



RWB2906

A range of manually operated winches for trailer boat use and many other general lifting applications (Not for lifting humans). These winches feature shaft and gears of stamped high tensile alloy steel with internally lubricated drum bushing and pinion gear shaft bearings for increased life and ease of operation. The frame has formed reinforcements for added strength and the winch is supplied with smooth turning roller grip handle. These winches are supplied with a black EDC corrosion resistant finish and are priced to suit the average budget. They are supplied **without** a winch cable - these must be ordered separately - see next 2 pages.

380KG (840LB) Capacity

3.2 to 1 gear ratio. One way single ratchet operation and freespool.

Base size : 95 x 88mm. 5 possible fastening positions.

RWB2903 Winch 380 Kg

SP214 Replacement handle only

545KG (1200LB) Capacity

4 to 1 gear ratio. Two way ratchet operation (winds mechanically both in and out) - and freespool operation.

Base size : 135 x 88mm. 5 possible fastening positions.

RWB2905 Winch 545 Kg

SP215 Replacement handle only

635KG (1400LB) Capacity

4 to 1 gear ratio. Two way ratchet operation (winds mechanically both in and out) - and freespool operation.

Base size : 135 x 88mm. 5 possible fastening positions.

RWB2906 Winch 635 Kg

SP215 Replacement handle only