

### C View SP (Suction & Pressure) Food & Beverage Hose

Specifically designed to outperform all other hoses in the beverage industry.

It is both a suction and pressure hose in one.

It is UV light resistant, conforms to AS2070 and EU2022-72-EC for use with food products and uses a plastic helix that will not rust or cut the hands of operators.

**Applications** Pressure or suction of any liquid or semi liquid that requires a food grade hose. Included are wineries, milk processing plants or tankers. Can be used with wine and spirits to 28 1/4 proof.

**Colour** Clear with Clear Rigid PVC Spiral

Temperature Range -5°C to +60°C

Chemical Resistance Excellent

Flexibility Excellent

Abrasion Resistance Excellent

Conforms to AS2070 & EU2002-72-EC



Product #	Nominal mm's		Vacuum Rating Kpa/20°C	Working Pres. @ 20°C		Weight kg/m	Min Bend in mm
	I.D	O.D.		Mpa	P.S.I		
206000	25.0	35.4	-90	1.2	175	0.68	130
206005	38.0	49.9	-90	1.2	175	1.01	220
206010	51.0	64.4	-90	1	145	1.67	300
206012	76.2	92.4	-90	1	145	2.57	490

### Standard Food Contact Milk Tanker

A general purpose suction/discharge hose for the transfer of food products, including beer, wine, drinking water and milk. Resistant to chemicals used in cleaning and is UV light resistant.

**Applications** Suitable for the tanker delivery of milk, other dairy products, drinking water, wine and other food products. The smooth bore enables easy cleaning and reduces bacteria buildup.

**Colour** Clear with Bone Rigid PVC Spiral

Temperature Range -5°C to +60°C

Abrasion Resistance Good

Conforms to AS2070 & EU2002-72-EC



Product #	Nominal mm		Vacuum Rating Kpa/20°C	Working Pres. @ 20°C		Weight kg/m	Min Bend mm
	I.D	O.D.		Mpa	P.S.I		
206400	25.2	32.0	-90	0.7	100	0.41	120
206410	31.8	39.0	-90	0.7	100	0.52	150
206420	38.4	46.2	-90	0.6	85	0.68	200
206430	50.8	60.0	-90	0.5	75	1.02	270
206440	63.7	74.3	-90	0.5	75	1.41	330
206450	76.0	89.0	-90	0.4	60	2.01	440
206460	102.2	116.0	-90	0.4	60	3.06	620