

Wine Food & Beverage Hose

Heavy duty flexible food quality PVC suction/discharge hose reinforced with a rigid spiral. Has a smooth bore to minimise flow losses and is UV light resistant.

Applications Suitable for the wine, canning and food packaging industries. It can be used for the suction of wine & spirits up to 28 1/4 proof.

The smooth bore enables easy cleaning and reduces bacteria buildup.

Colour Clear with Claret Spiral

Temperature Range -5°C to +60°C

Chemical Resistance Excellent

Flexibility Good

Abrasion Resistance Excellent

Conforms to AS2070 & EU2002-72-EC



Product #	Nominal mm's		Vacuum Rating Kpa/20°C	Working Pres. @ 20°C		Weight kg/m	Min Bend mm
	I.D.	O.D.		Mpa	P.S.I		
206500	25.2	34	-90	0.7	100	0.6	160
206510	31.8	41	-90	0.7	100	0.71	190
206520	38.4	48	-90	0.6	85	0.82	230
206530	50.8	62	-90	0.5	75	1.2	290
206540	63.7	76	-90	0.5	75	1.73	360
206550	76	90	-90	0.5	75	2.29	450
206560	102.2	117	-90	0.4	60	3.33	640
206570	127.8	143	-90	0.4	60	4.58	900
206580	150	170	-90	0.35	50	6.75	1200

C View S Food & Beverage Hose

An exceptionally flexible, clear suction/discharge hose suitable for food and

beverages. The clear rigid helix makes the hose completely transparent. It is UV light

resistant and conforms to AS2070 1999 and EU2022-72-EC.

Applications Suction of any fluid that requires a food grade hose including wineries, milk collection or processing, canneries, and food processing plants. It can be used for the suction or delivery of wine & spirits to 28 1/4 proof.

Colour Clear with Clear Rigid PVC Spiral

Temperature Range -5°C to +60°C



Product #	Nominal mm's		Vacuum Rating Kpa/20°C	Working Pres. @ 20°C		Weight kg/m	Min Bend mm
	I.D.	O.D.		Mpa	P.S.I		
206482	25	32	-90	1	145	0.43	120
206484	32	39.6	-90	0.9	130	0.65	150
206486	38	45.8	-90	0.9	130	0.7	200
206488	50.8	60.2	-90	0.7	102	1.05	270
206490	63.5	73.5	-90	0.6	87	1.44	330
206492	76.2	87.8	-90	0.6	87	1.98	440
206494	101.6	114.4	-90	0.5	73	3.14	620