


11 GALLON



11 GAL Side Mount, 120V, Front Heat Exchange 11840

- Dimensions: 18.875 in W x 16.25 in H x 21.625 in D
- Mount Arrangement: Side-Side
- Electrical Input: 120V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA



11 GAL Side Mount, 240V, Front Heat Exchange 11850

- Dimensions: 18.875 in W x 16.25 in H x 21.625 in D
- Mount Arrangement: Side-Side
- Electrical Input: 240V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

11 GAL Side Mount, 240V, Front Heat Exchange 11860

- Dimensions: 18.875 in W x 16.25 in H x 21.625 in D
- Mount Arrangement: Side-Side
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA




11 GAL Front Mount, 120V, Front Heat Exchange 11841

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 120V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

11 GAL Front Mount, 240V, Front Heat Exchange 11851

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA



11 GAL Front Mount, 240V, Front Heat Exchange 11861

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA




**11 GAL Front Mount, 120V, Rear Heat Exchange
11842**

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 120V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

**11 GAL Front Mount, 240V, Rear Heat Exchange
11852**

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA



**11 GAL Front Mount, 240V, Rear Heat Exchange
11862**

- Dimensions: 16.25 in W x 16.25 in H x 23.25 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA