

6 GALLON




6 GAL Side Mount, 120V, Front Heat Exchange 11810

- Dimensions: 15.625 in W x 13.625 in H x 19.375 in D
- Mount Arrangement: Side-Side
- Electrical Input: 120V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

6 GAL Side Mount, 240V, Front Heat Exchange 11820

- Dimensions: 15.625 in W x 13.625 in H x 19.375 in D
- Mount Arrangement: Side-Side
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA



6 GAL Side Mount, 240V, Front Heat Exchange 11830

- Dimensions: 15.625 in W x 13.625 in H x 19.375 in D
- Mount Arrangement: Side-Side
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA



6 GAL Front Mount, 120V, Front Heat Exchange 11811


- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 120V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

6 GAL Front Mount, 240V, Front Heat Exchange 11821

- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

6 GAL Front Mount, 240V, Front Heat Exchange 11831

- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA





**6 GAL Front Mount, 120V, Rear Heat Exchange
11812**

- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 120V - 60Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

**6 GAL Front Mount, 240V, Rear Heat Exchange
11822**

- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 50Hz/1500W
- Wiring Configuration: L1 & N
- T&P Valve Type: 150psi & 210° F, CSA

**6 GAL Front Mount, 240V, Rear Heat Exchange
11832**

- Dimensions: 13.75 in W x 13.625 in H x 19.75 in D
- Mount Arrangement: Front-Rear
- Electrical Input: 240V - 60Hz/1500W
- Wiring Configuration: L1 & L2
- T&P Valve Type: 150psi & 210° F, CSA

