

**PERFORMANCE YACHT FITTINGS - CAM CLEATS**

Part No.- PYF10

Small Cam Cleat - Bush Bearing  
Hole Spacing: 27mm

Spare Part - PYF10SP Spring Only



Part No.- PYF101

Black Swivel Control Cleat  
Hole Spacing: 27mm



Part No.- PYF102

Black Swivel Control Cleat including small cam



Part No. - PYF103

Black Swivel Control Cleat including medium cam



Part No.- PYF104

Black Swivel Control Cleat

PYF101 with Riley RM162 cam cleat which assists the sheet in swivelling the unit

Weight: 110g



Part No.- PYF12

Small Cam Cleat including Lead - Bush Bearing

Hole Spacing: 27mm



Part No.- PYF15

Small Cam Cleat - Lead

The rope guide, made from stainless steel, fits neatly under the parallel base (PYF10 & PYF12), ensuring a true lead into the cleat.



Part No.- PYF16

15° Wedge & Backing Plate

The angled base is used where a mounting surface is not conveniently aligned with the rope. Proper alignment of the cleat ensures correct cleating, and minimum resistance to free rope movement during adjustment. Special moulded washers are provided to correctly clamp the underside of the cleat fixture, preventing damage to softer deck materials.

Fits RM161 & RM162 and PYF10 & PYF12



Part No.- PYF17

Small Fluro Backing Plate & Plugs - 3 Pack  
Fluro colours - Pink, Green & Yellow  
Fits Small Cam Cleats - PYF10 & PYF12



Part No.- PYF20

Medium Cam Cleat - Bush Bearing  
Hole Spacing: 38mm

Spare Part - PYF20SP Spring Only



Part No.- PYF21

Medium Cam Cleat - Bush Bearing  
With Stainless Steel Teeth insert  
Hole Spacing: 38mm



Part No.- PYF24

Medium Cam Cleat - Roller Bearing  
Hole Spacing: 38mm



Part No.- PYF30

Medium Cam - Lead Kit

The rope guide, made from stainless steel, fits neatly under the parallel base, ensuring a true lead into the cleat.

Hole Spacing: 38mm



---

Part No.- PYF31

Medium Cam - Flat Spacer Pad

Hole Spacing: 38mm



---

Part No.- PYF32

Medium Cam - Flat Spacer Pad

Hole Spacing: 38mm

