

BRAKE HAND WINCH

Brake Winches are compact, lightweight and a cost-effective solution for a variety of applications. They can be used for both pulling and lifting purposes and comply to the Australian Standards AS1418.2 when correctly fitted with the approved wire rope and fittings. They can be supplied with a powder-coated, a marine-coated corrosion resistant finish or in stainless steel, depending on your application.

OPC Kylan Coating is a new and unique process which uses baked-on, non-toxic, environmentally friendly, organic, macromolecular monomer coating compound. This, combined with aluminium and zinc, provides a highly corrosion resistant coating on steel. By using OPC Kylan Coating with stainless steel fasteners and fittings on all of the winches, this unique range of corrosion resistant winches can stand up to over 1000 hours of salt spray testing.

- Positive Weston-style brake will hold the load in any position.
- Compact, lightweight and rugged construction.
- Mechanical components enclosed for protection and safety.
- Available with a powder-coated or a marine-coated corrosion resistant finish.
- BHW1200 available as a noiseless model
- S1418.2 Compliance applies when correctly fitted with approved wire rope and fittings.
- BHW models available with marine-coated Kylan finish.
- BHW1200 / BHW1800 / BHW2600 also available in stainless steel.
- Heat-treated gears.
- Strong removable handles.
- High precision construction minimises gear noise.

CODE	Pulling Capacity (kg)	Lifting Capacity	Hand Force Required (kg)	Standard Finish	Gear Ratio	Handle Length (mm)	Hub Dia. (mm)	Cable Dia. (mm)	Net Weight (kg)	Kylan Finish Avail.	Stainless Steel Avail.	Noiseless Avail.
	370	180	14.5	powder	4.1 : 1	160	40	4.1	3.0	yes	no	no
	545	270	15	powder	4.1 : 1	210	50	4.8	3.3	yes	yes	yes
	820	410	22	powder	5.0 : 1	320	70	6.4	8.0	yes	yes	no
	1200	600	19	powder	10 : 1	320	80	8.0	10.3	yes	yes	no
	1700	850	16	powder	22.2 : 1	300	60	6.4	13.5	yes	no	no



Powder Coated



Kylan Coated



Powder Coated